



PRODUCT NAME **TEFCOTE PLASTER PRIMER**

Product Function Priming of Plaster, Plasterboards and any other porous surfaces.

Packaging 25 Litre
Issue Date – November 2002

Features

A premium quality and easy to apply water-based primer for porous surfaces. Tefcote Plaster Primer has a very good penetration on fine porous and high-density surfaces and therefore achieves a very good adhesion of subsequent materials i.e. paint, fibreglass etc.

Technical Data

Type: Water based Styrene-acrylic dispersion
Colour: White
Viscosity: approx. 10 sek. (Din 4)
Solids content: approx. 17 %
Specific gravity: approx. 1,0 kg/ltr

Storage

Shelf life: Minimum 12 months in tightly closed packing if stored dry and cool. The product should be protected from frost.

Preparation

Preparation: The surface must be clean, dry and free from dust.
Dilution: If Tefcote Plaster Primer is used before mounting of wallpaper it can be diluted 1:1 with water.
Application: The primer is applied in an even layer with a brush, a roller or a spray gun. If the surface is very absorbing, the primer should be applied in 2 layers.
Coverage: 5-10 m²/l depending on how absorbing the surface is.
Drying time: 2-3 hours.

Cleaning

Uncured primer can be removed with water.

Safety

Before use, refer to our Material COSHH Safety Data Sheet.

INFORMATION PROVIDED IN THIS LEAFLET IS GIVEN IN GOOD FAITH BUT WITHOUT WARRANTY ON THE UNDERSTANDING THAT USERS SATISFY THEMSELVES ABOUT THE PRODUCTS SUITABILITY FOR THEIR OWN PURPOSE.

ANY SALE BY THIS COMPANY IS STRICTLY SUBJECT TO OUR CONDITIONS OF SALE.